



# DIGITORQON™ DTM-Series

BOLTING SOLUTION COMPANY



- Tightening torque measurement works in both clockwise and counter-clockwise direction
- Digital read - out & SD Storage of Tightening Torque
- High repeated accuracy:  $\pm 3\%$
- Calibration Certificate Included




Model	Reading Range	Reading Accuracy	Battery	Battery Life	Operating Temperature	Adaptable Model	Dimensions				Weight	
							(mm)		(Inch)		(kg)	(lb)
							D	L	D	L		
DTM5EN DTM5EF	100 – 550 (DTM5EN) N·m 80 – 400 (DTM5EF) lbf·ft	$\pm 3\%$	AAA Alkaline x 4 or Nickel Metal Hydride Rechargeable Battery	Approx 10,000 readings	0-40°C / 32-104°F, humidity below 80% (no condensation allowed)	GSR51E/GSR52E GSR31E-CE/GSR32E-CE GSR31E-UC/GSR51E-CE GSR52E-CE/GSR51E-UC	95	117	3.7	4.6	1.7	3.7
DTM8EN DTM8EF	250 – 850 (DTM8EN) N·m 180 – 620 (DTM8EF) lbf·ft					GSR71E/GSR72E GSR81E-CE/GSR82E-CE GSR81E-UC	95	117	3.7	4.6	1.7	3.7
DTM12EN DTM12EF	550 – 1250 (DTM12EN) N·m 410 – 920 (DTM12EF) lbf·ft					GSR121E/GSR122E GSR121E-CE/GSR122E-CE GSR121E-UC	106	124	4.2	4.9	2.4	5.3
DTM21EN DTM21EF	840 – 2180 (DTM21EN) N·m 620 – 1590 (DTM21EF) lbf·ft					GSR211E/GSR212E GSR211E-CE/GSR212E-CE GSR211E-UC	115	129	4.5	5.1	3.0	6.6

\*New DTM models for GNR series 4000Nm, 8000Nm, 10000Nm (2950lbf·ft, 4430lbf·ft, 7380lbf·ft) coming soon.

### Standard Accessories

Hex Key Wrench (4mm)	1	Calibration Certificate with Traceability Diagram	1
(-) Screw Driver	1	Metal Case	1
AAA Alkaline Battery	4	microSD Memory Card Set	1
Instruction Manual	1		



Manufactured by  
**TONE CO., LTD.**  
OSAKA, JAPAN.

web site <http://www.tonetool.co.jp>  
e-mail: [overseas@tonetool.co.jp](mailto:overseas@tonetool.co.jp)

Specifications and the design are subject to change without notice.  
The company has accreditation to ISO14001 and ISO9001.

Your Distributor



JM Tor Par SA de CV  
Tel. (0155) 5082-0180  
[ventas@jmtorpar.com](mailto:ventas@jmtorpar.com)  
[sales@jmtorpar.com](mailto:sales@jmtorpar.com)  
[www.jmtorpar.com](http://www.jmtorpar.com)